



The VERSITRON MCC-16 Intelligent Media Converter Chassis family serves as a 16-slot converter center, wiring concentrator, and central power supply for all of the VERSITRON standalone media converters. A wide range of media converters are available depending on your requirements. Each standalone media converter can be easily installed into the chassis, and are hot-swappable. The MCC-16 supports optional console, telnet, Web-based, SNMP, and event SNMP trap management interfaces.

KEY FEATURES

- Managed Media Converter Chassis
- 19-inch rack mountable; 2U high
- Supports up to 16 media converters with hot-swappable installation
- Supports console, telnet, Web-based, SNMP, and event SNMP trap management
- Software upgrade via TFTP
- Supports 90-264VAC and optional – 48VDC power supply
- Optional full power supply redundancy (dual power line inputs) available
- Highly modular design
- Visible system status indicators
- Management from anywhere and any platform using a Web browser
- Easy to use point and click user interface
- Supports VERSITRON full line of media converters (See table on Page 2)

CHASSIS SPECIFICATIONS

	<u>MCC-16</u>	<u>MCC-16R</u>	<u>MCC-16M</u>	<u>MCC-16RM</u>
Model				
19-inch Rack Mount	Yes	Yes	Yes	Yes
Power Supplies	1	2	1	2
Management Support	No	No	Yes	Yes
Management Module	None	None	Installed	Installed
Number of converter slots	16	16	16	16
Input Voltage (VAC)	90-246	90-246	90-246	90-246
Power Supply	60W	60W	60W	60W
Weight *	12.1lbs (5.5kg)	13.7lbs (6.2kg)	12.1lbs (5.5kg)	13.7lbs (6.2kg)
Height	3.47 in. (88 mm)			
Dimension	17.45 x 3.47 x 11.82 in. (443 x 88 x 300 mm)			
Relative Humidity	5% ~ 95% non-condensing			
Temperatures	Operating: -5°C to 40°C Storage: -20°C to 80°C			
LEDs	Power 1, Power 2, Status for: CPU, Fan, Console Rx, LAN port link			

* With 1 or 2 AC power supplies, management module and no converters



MEDIA CONVERTERS SUPPORTED		
Model #	Data Rate	Description
M7273S	10/100	10/100Base-TX to 100Base-FX Media Converter, Duplex Multi-Mode, ST Connectors
M7274S	10/100	10/100Base-TX to 100Base-FX Media Converter, Duplex Multi-Mode, SC Connectors
M7275S-x	10/100	10/100Base-TX to 100Base-FX Media Converter, Duplex Single-Mode, SC Connectors
M7275S-2SFA	10/100	10/100Base-TX to 100Base-FX Media Converter, Simplex Single-Mode, SC Connectors
M7275S-2SFB	10/100	10/100Base-TX to 100Base-FX Media Converter, Simplex Single-Mode, SC Connectors
M7250	1000	1000Base-T to 1000Base-X Media Converter, SFP Module with LC Connectors
M7260	10/100/1000	10/100/1000Base-T to 1000Base-X Media Converter, SFP Module with LC Connectors



M727x
10/100Base-TX
to
100Base-FX



M7250
1000Base-T
to
1000Base-X



M7260
10/100/1000Base-T
to
1000Base-X

Front and rear views shown above.



FCC Part 15, Class A
CISPR 22 Class A

VERSITRON, Inc.

83 Albe Drive / Suite C • Newark, DE 19702
Phone: 302-894-0699 / 800-537-2296 Fax: 302-894-0624
www.versitron.com

OCT2006
MCC-16
Media Converter Chassis